




**U2**  
MobileS

**Designed to Print on Everything**  
Introducing New U2 MobileS Ink Jet Printer

# We Got You Covered



Coated Paper




Metal & Aluminum



Hard Plastic



Flexible Plastic



Construction Materials



## U2 MobileS Specifications

|                     |                                                                                                                                                                                                                 |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display             | 3.5" color LCD with LED backlight                                                                                                                                                                               |
| User Interface      | Simple and easy-to-use operating system                                                                                                                                                                         |
| Input Device        | Pocket-sized IR remote keypad                                                                                                                                                                                   |
| Available Languages | English, Chinese (Traditional), Chinese (Simplified), Japanese, Russian, Korean, German, Portuguese, Spanish, French, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Polish |
| Print Engine        | HP Thermal Ink Jet Technology                                                                                                                                                                                   |
| Print Resolution    | Max 300*400 dpi                                                                                                                                                                                                 |
| Print Distance      | Max 1663.7 mm                                                                                                                                                                                                   |
| Message High        | Alphanumeric, logos, date/time, shift code, counter, lot box code                                                                                                                                               |
| Print Capability    | Up to 4 lines and 12.7mm (0.5")<br>selectable front size from 2.7mm to 12.7mm                                                                                                                                   |
| Barcodes            | EAN8, EAN13, EAN14, EAN128, UPCA, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QR Code and 2D barcode                                                          |
| Data Interface      | USB2.0*1, RS-485*1                                                                                                                                                                                              |
| Dimensions          | 143.5 (L) x 219 (W) x 143 (H) mm                                                                                                                                                                                |
| Weight              | 1.13 kg (2.49 lbs)                                                                                                                                                                                              |

## Long Lasting Battery

|                               |                                  |
|-------------------------------|----------------------------------|
| Rated Capacity                | 1,840 mAh                        |
| Standard Voltage              | 11.1V                            |
| Input/Output Voltage          | 12.6V                            |
| Charging Voltage              | 12.6V                            |
| Charging Temperature Range    | 0°C - 45°C (32°F - 113°F)        |
| Discharging Temperature Range | -20°C - 60°C (-4°F - 140°F)      |
| Dimensions                    | 100.3 (L) x 56.3 (W) x 21 (H) mm |
| Weight                        | 150g (0.33 lbs)                  |
| Cycle Life                    | More than 300 cycles             |

## Ink Solution

A wide range of ink selections for printing on porous, semi-porous and non-porous substrates

## Environment

|                             |                             |
|-----------------------------|-----------------------------|
| Operation Temperature Range | 5°C - 40°C (41°F - 104°F)   |
| Storage Temperature Range   | -20°C - 70°C (-4°F - 158°F) |



WWW.ANSER-U2.COM